

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: ALL SOLV EXTREME CS01

SECTION 1: PRODUCT INFORMATION

PRODUCT NAME: All Solv Extreme

MANUFACTURER: Bridgepoint Systems

4282 S 590 W

Salt Lake City, UT 84123 Telephone: 801-261-1282

Prepared 7/13/2012

EMERGENCIES: (800) 535-5053 (Infotrac)

Hazard Rating (Zero=Insignificant 1= Slight 2= Moderate 3= High 4= Extreme)

Fire: 4 Health:2 Reactivity:0

SECTION 2: INGREDIENTS

PRINCIPLE HAZARDOUS INGREDIENTS: OSHA PEL

Glycol Ether DB (CAS # 112-34-5) N/A

Acetone (CAS # 67-64-1) 1000 p.p.m.

Isopropyl Alcohol (CAS # 67-63-0) 400 p.p.m.

SECTION 3: HEALTH HAZARD INFORMATION

Route(s) of entry Eyes? yes Skin? Yes Inhalation? Yes Ingestion? Yes

Health Hazards: Eyes – May cause irritation. Skin – May cause irritation.

Inhalation - Excessive exposure may cause respiratory irritation

Ingestion - Large amounts may be harmful

Carcinogenicity: NTP: Known - No; Anticipated - No OSHA: TLVA4 for Acetone &

Isopropyl Alcohol IARC: No

SECTION 4: EMERGENCY AND FIRST AID PROCEDURES

Eyes...... Flush thoroughly with water for 15 minutes. Get medical attention. Skin...... Flush thoroughly with water for 15 minutes. Get medical attention.

Inhalation... Move to fresh air. Get medical attention if irritation occurs.

Ingestion... Do not induce al vomit unless directed to do so by medical personnel. Get

medical attention if irritation occurs.

MATERIAL SAFETY DATA SHEET PRODUCT NAME: ALL SOLV EXTREME CS01

Page 2 of 4

SECTION 5: FIRE, EXPLOSION & REACTIVITY DATA

Flash Point: <20 ° F (FCC) Boiling Point: 194 ° F

Extinguishing Media: Use water, carbon dioxide, dry powder or other media

appropriate for materials actually involved in fire.

Special Fire Fighting Procedures: In the event of a fire, wear full protective clothing and NIOSH-approved, self-contained breathing apparatus with full facepiece operated in the

pressure demand or other positive pressure mode. Unusual Fire and Explosion Hazards: None

SECTION 6: ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Absorb liquid on inert material such as vermiculite, and dry sand.

LARGE SPILL: Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source, contain area of spill to prevent spreading, pump liquid to salvage tank. Remaining liquid may be absorbed with inert material such as dry sand, vermiculite, and shoveled into containers. Prevent run-off to sewers, streams, or other bodies of water. If run-off occurs, notify the proper authorities as required that a spill has occurred.

SECTION 7: PRECAUTIONS FOR HANDLING AND STORAGE

Store out of reach of children. Keep container tightly closed as acetone tends to volatize out of even sealed bottles over time. . Store in a cool, dry location. Avoid freezing or extended storage in high temperatures.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Airborne Exposure Limits..... None established.

SECTION 9: PHYSICAL DATA

Odor: Slight Solvent Physical State: Liquid. Appearance: Clear

pH: N/A

Specific Gravity: 0.935 g/mL

Boiling Point: 194 ° F

Freezing/Melting Point: N/E

Vapor Pressure: N/E Vapor Density: N/E

Solubility in Water: Miscible

MATERIAL SAFETY DATA SHEET PRODUCT NAME: ALL SOLV EXTREME CS01

Page 3 of 4

SECTION 10: STABILITY AND REACTIVITY

Stability: Stable under ordinary conditions of use and storage.

Hazardous Decomposition or Byproducts: Exposure to fire may liberate carbon dioxide, carbon monoxide, and other unidentified thermal decomposition products from this product or its packaging.

Hazardous Polymerization: Will not occur.

Incompatibilities: Acid materials and strong oxidizing materials.

Conditions to Avoid: None known

SECTION 11: TOXICOLOGICAL INFORMATION

Acetone - Oral Rat LD50: 5800 mg.kg. Inhalation Rat LC50: 100 mg/m3, irritation eye rabbit, standard draize, 20 mg severe; investigated as a tumorigen, mutagen, reproductive effector.

Glycol Ether DB -Oral Rat LD50: 7,292 mg/kg Dermal Rabbit LD-50: 2,764 mg/kg Skin Irritation (rabbit) slight Eye Irritation (rabbit) moderate

SECTION 12: ECOLOGICAL INFORMATION

Environmental Fate.......Acetone readily biodegrades.

Environmental Toxicity...... Acetone not toxic to fish. Glycol Ether DB Acute Aquatic Effects Data: 24 h LC-50 (goldfish): 2700 mg/L 96 h LC-50 (bluegill sunfish): 1300 mg/L

SECTION 13: DISPOSAL CONSIDERATIONS

Do not dispose of on the land, in surface waters, sewers or in storm drains. Larger quantities should be collected for reuse or consigned to a licensed hazardous waste hauler for disposal in accordance with federal, state and local regulations. <u>All</u> disposal <u>must be</u> in accordance with all federal, state and local regulations.

SECTION 14. TRANSPORTATION

Ground Transportation: Limited quantity exception applies for inner packaging not over .3 gallons (1 liter). Requires a limited quantity label.

Air Transportation: UN1993; Flammable Liquid, N.O.S., (Acetone); 3: II. Check regulation for limited quantity exceptions.

Maritime Transportation: UN1993; Flammable Liquid, N.O.S., (Acetone); 3: II. Check regulation for limited quantity exceptions.

MATERIAL SAFETY DATA SHEET PRODUCT NAME: ALL SOLV EXTREME CS01

Page 4 of 4

SECTION 15: REGULATORY INFORMATION

Acetone (CAS # 67-64-1) CERCLA, SARA 313 Glycol Ether DB (CAS # 111-76-2) SARA 313 Isopropanol (CAS #67-63-0 <2%) MASS, NJHS, NRC, OSHAWAC, PA, SARA 313, TXAIR, WHMIS 1% All components are listed on TSCA

CERCLA = Comprehensive Environmental Response, Compensation, and Liability Act MASS = Massachusetts Hazardous Substance List
NJHS = New Jersey Right-toKnow Hazardous Substances
NRC = Nationally Recognized Carcinogens
OSHA WAC = OSHA Workplace Contaminants
PA = PA Right-to-Know List of Hazardous Substances
SARA 313 = SARA 313 Title III Toxic Chemicals
TXAIR = Texas Air Contaminants with Health Effects Screening Level
WHMIS = Workforce Hazardous Material Information System

SECTION 16: OTHER INFORMATION

This product has no established regulatory information. All regulatory information given is based on individual components of the mixture by component number. While this information and recommendations set forth herein are believed to be accurate and reliable, it is provided without warranty regarding its accuracy. BRIDGEPOINT SYSTEMS MAKES NO WARRANTY WITH RESPECT HERETO AND DISCLAIMS ALL LIABILITY FROM RELIANCE THEREON. Users must determine safe conditions for use and assume liability for any loss, injury, damage or expense resulting from use of this product.

N/A= Not applicable N/D= Not determined N/E= Not established