

SAFETY DATA SHEET

HYDRO-FORCE™

Issuing date 08-May-2015

Revision Date 08-May-2015

Version 1

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Label Name

Hydro-Force - Viper Venom

Other means of identification

Not applicable

UPC Code(s) Product code

CR22

UN/ID No Synonyms UN3266 None

Recommended use of the chemical and restrictions on use

Recommended Use

Specialty cleaner. Tile and grout cleaner.

Uses advised against

Follow label instructions. Not recommended for any use except intended use.

Supplier's details

Supplier Address

Manufacturer Address

Hydro-Force

Hydro-Force

4282 South 590 West

4282 South 590 West Salt Lake City, UT 84123

Salt Lake City, UT 84123

USA

USA

Emergency telephone number

Company Phone Number

1-801-268-2673

Company Emergency Phone

United States: 1-800-535-5053 (INFOTRAC - 24 hours, 7 days a week)

Number

International: 1-352-323-3500 (INFOTRAC – 24 hours, 7 days a week)

Emergency telephone

Poison Control 1-800-222-1222 (24 hour)

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Inhalation (Gases)	Category 4	
Skin corrosion/irritation	Category 1C	
Serious eye damage/eye irritation	Category 1C	

GHS Label elements, including precautionary statements

Emergency Overview

Danger

Hazard Statements

Harmful if inhaled

Causes severe skin burns and eye damage



Appearance Clear Liquid

Physical state liquid

Odor No information available

Precautionary Statements - Prevention

Use only outdoors or in a well-ventilated area
Do not breathe dust/fume/gas/mist/vapors/spray

Wash face, hands and any exposed skin thoroughly after handling

Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response

Immediately call a POISON CENTER or doctor/physician

Call a POISON CENTER or doctor/physician if you feel unwell

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower Wash contaminated clothing before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other information

- · May be harmful in contact with skin
- May cause respiratory irritation General Hazards

Keep out of reach of children

Please see Section 11. Toxicological Information for further information

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %	Trade Secret
Butoxyethanol	111-76-2	1 - 5	*
Diethylene glycol monobutyl ether	112-34-5	1 - 5	*
Sodium Hydroxide	1310-73-2	1 - 5	*

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

First aid measures for different exposure routes

General advice

Immediate medical attention is required.

Eye contact

Immediate medical attention is required. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected

area.

Skin contact

If skin irritation persists, call a physician. Wash off immediately with soap and plenty of water

while removing all contaminated clothes and shoes.

Toxic - Inhalation

Move to fresh air. Call a physician or Poison Control Center immediately. If not breathing,

give artificial respiration. If breathing is difficult, give oxygen.

Ingestion

Immediate medical attention is required. Do NOT induce vomiting. Drink plenty of water. Never give anything by mouth to an unconscious person. Remove from exposure, lie down. Clean mouth with water and drink afterwards plenty of water. Call a physician or Poison

Control Center immediately.

Protection of First-aiders

Use personal protective equipment. Avoid contact with skin, eyes and clothing.

Most important symptoms/effects, acute and delayed

Main Symptoms

No information available.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood pressure may occur with moist rales, frothy sputum, and high pulse pressure. Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

The product causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to release of irritating gases and vapors. In the event of fire and/or explosion do not breathe fumes.

Hazardous Combustion

Products

No information available.

Explosion Data

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions

Evacuate personnel to safe areas. Use personal protective equipment. Avoid contact with skin, eyes and clothing. Keep people away from and upwind of spill/leak.

Other information

Refer to protective measures listed in Sections 7 and 8.

Advice for emergency responders

For personal protection see section 8.

Environmental precautions

Environmental precautions

Do not allow material to contaminate ground water system. Should not be released into the environment. Prevent further leakage or spillage if safe to do so. Prevent product from

entering drains.

Methods and materials for containment and cleaning up

Methods for Containment

Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Dike far ahead of liquid spill for later disposal. Soak up with inert absorbent material. Take up. mechanically, placing in appropriate containers for disposal. Clean contaminated surface thoroughly. Prevent product from entering drains. Dam up. After cleaning, flush away traces with water.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling

Wear personal protective equipment. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Handle product only in closed system or provide appropriate exhaust ventilation at machinery.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage

conditions

Keep out of the reach of children. Keep containers tightly closed in a dry, cool and

well-ventilated place. Keep in properly labeled containers.

Packaging material

Keep product in packaging product is initially sold in.

Incompatible products

Incompatible with strong acids and bases. Incompatible with oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Butoxyethanol 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m³ (vacated) S*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m³
Diethylene glycol monobutyl ether 112-34-5	TWA: 10 ppm inhalable fraction and vapor		
Sodium Hydroxide 1310-73-2	Ceiling: 2 mg/m ³	TWA: 2 mg/m³ (vacated) Ceiling: 2 mg/m³	IDLH: 10 mg/m ³ Ceiling: 2 mg/m ³

NIOSH IDLH: Immediately Dangerous to Life or Health

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F,2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Measures

Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/Face Protection

Tightly fitting safety goggles. Face-shield.

Skin and body protection

Protective gloves

Respiratory protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene measures

Remove and wash contaminated clothing before re-use. When using, do not eat, drink or smoke. Keep away from food, drink and animal feeding stuffs. Contaminated work clothing should not be allowed out of the workplace. Provide regular cleaning of equipment, work area and clothing. Avoid contact with skin, eyes and clothing. For environmental protection, remove and wash all contaminated protective equipment before re-use. Wear suitable gloves and eye/face protection.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and chemical properties

Physical state

liquid

Appearance Color

Clear Liquid

No information available

Odor Odor threshold

125

Characteristic

No information available

Remarks • Method

Property Hq

Melting point

<u>Values</u>

12.5

No information available

Boiling point/boiling range Flash Point

No information available No information available

Evaporation rate

No information available

Flammability (solid, gas) Flammability Limits in Air No information available

Upper Flammability Limit Lower Flammability Limit Vapor pressure

No information available No information available No information available No information available

Vapor density **Specific Gravity**

1.015

Water solubility Solubility in other solvents

Soluble in water No information available

Partition coefficient: n-octanol/waterNo information available Autoignition temperature Decomposition temperature

No information available No information available

Viscosity, kinematic

200 cps

Viscosity, dynamic Explosive properties **Oxidizing Properties**

No information available No information available No information available

Other information

Softening point Molecular weight VOC Content(%)

No information available No information available No information available

Density VALUE 1.015

Bulk Density VALUE

No information available

10. STABILITY AND REACTIVITY

Reactivity

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Hazardous Polymerization

None under normal processing.

Conditions to Avoid

Exposure to air or moisture over prolonged periods.

Incompatible Materials

Incompatible with strong acids and bases. Incompatible with oxidizing agents.

Hazardous Decomposition Products

Thermal decomposition can lead to release of irritating gases and vapors.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Toxic - Inhalation

Harmful by inhalation. Toxic by inhalation. Avoid breathing vapors or mists. May cause

irritation of respiratory tract.

Eye contact

Avoid contact with eyes. May cause burns.

Skin contact

Avoid contact with skin. May cause burns.

Ingestion

Do not taste or swallow. Ingestion may cause irritation to mucous membranes. Ingestion

causes burns of the upper digestive and respiratory tracts.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Butoxyethanol 111-76-2	= 470 mg/kg (Rat)	= 220 mg/kg (Rabbit)	= 450 ppm (Rat) 4 h
Diethylene glycol monobutyl ether 112-34-5	= 3384 mg/kg (Rat)	≃ 2700 mg/kg (Rabbit)	•
Sodium Hydroxide 1310-73-2		= 1350 mg/kg (Rabbit)	

Information on toxicological effects

Symptoms

No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Eye damage/irritation No information available. No information available.

Sensitization

No information available. No information available.

Germ Cell Mutagenicity Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Butoxyethanol	A3	Group 3		
111-76-2		•		

ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

STOT - repeated exposure

IARC: (International Agency for Research on Cancer) Group 3 - Not Classifiable as to Carcinogenicity in Humans

Reproductive toxicity
Developmental Toxicity
STOT - single exposure

No information available. No information available.

No information available.

No information available.

Viper Venom

Revision Date 08-May-2015

Chronic toxicity

Chronic exposure to corrosive fumes/gases may cause erosion of the teeth followed by jaw

necrosis. Bronchial irritation with chronic cough and frequent attacks of pneumonia are common. Gastrointestinal disturbances may also be seen. Avoid repeated exposure.

Possible risks of irreversible effects. May cause adverse liver effects.

Target Organ Effects

Blood, Central nervous system, Eyes, Hematopoietic System, Kidney, Liver, Respiratory

system, Skin.

Aspiration hazard

No information available.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document.

ATEmix (oral)

7393 mg/kg

ATEmix (dermal)

3852 mg/kg

ATEmix (inhalation-gas)

14143 mg/l

ATEmix (inhalation-dust/mist)

30.3 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

0% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia and other aquatic invertebrates
Butoxyethanol 111-76-2		1490: 96 h Lepomis macrochirus mg/L LC50 static 2950: 96 h Lepomis macrochirus mg/L LC50	1000: 48 h Daphnia magna mg/L EC50
Diethylene glycol monobutyl ether 112-34-5	100: 96 h Desmodesmus subspicatus mg/L EC50	1300: 96 h Lepomis macrochirus mg/L LC50 static	100: 48 h Daphnia magna mg/L EC50
Sodium Hydroxide 1310-73-2		45.4: 96 h Oncorhynchus mykiss mg/L LC50 static	

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical Name	Partition coefficient
Butoxyethanol	0.81
111-76-2	

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment

Waste Disposal Methods

This material, as supplied, is a hazardous waste according to federal regulations (40 CFR

261).

Contaminated packaging

Do not re-use empty containers.

US EPA Waste Number

D002

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
Sodium Hydroxide	Toxic
1310-73-2	Corrosive

14. TRANSPORT INFORMATION

DOT

UN/ID No

UN3266

Proper shipping name

Corrosive liquid, basic, inorganic, n.o.s. (Sodium Hydroxide)

Hazard class

8

Packing Group

Ш Sodium hydroxide: RQ lb.= 1000

Reportable Quantity (RQ) **Special Provisions**

IB3, T7, TP1, TP28

Emergency Response Guide

154

Number

Quantity Limits

Inner packaging not over 5.0 L (1.3 gallons) net capacity each for liquids

IMDG - Maritime Transportation

UN/ID No

UN3266

Proper shipping name

Corrosive liquid, basic, inorganic, n.o.s. (Sodium Hydroxide)

Hazard class

Ш

Packing Group EmS No.

F-A, S-B

Special Provisions

Check regulations for limited quantity exceptions

Do not ship by air unless within allowed limits

IATA - Air Transportation

UN/ID No

Proper shipping name

Hazard class **Packing Group** Special Provisions

15. REGULATORY INFORMATION

International Inventories

TSCA

Complies

DSL/NDSL

Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical Name	SARA 313 - Threshold Values %
Butoxyethanol - 111-76-2	1.0
Diethylene glycol monobutyl ether - 112-34-5	1.0
SARA 311/312 Hazard Categories	

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous
		- TOXIOT SHARES	OTTA- I HOLLY I ONGIANS	CHA-Hazaidous
L	Quantities]	Substances
	······································	L	· · · · · · · · · · · · · · · · · · ·	- 4001411000

Sodium Hydroxide	1000 lb	!	v
4040.70.0	100010]	_ ^
1310-73-2		i i	
AFRAL A			

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Sodium Hydroxide 1310-73-2	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Butoxyethanol 111-76-2	X	X	X
Diethylene glycol monobutyl ether 112-34-5	Х		X
Sodium Hydroxide 1310-73-2	Х	X	X
Sodium Sulfate 7757-82-6		X	Х

U.S. EPA Label information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION

NFPA

Health hazard 3

Flammability 1

Instability 0

Physical and chemical

hazards -

HMIS

Health hazard 3

Flammability 1

Physical Hazard 0

Personal protection X

Prepared By

Hydro-Force

Environmental Health & Safety

Revision Date

Revision Note

08-May-2015

No information available

Disclaimer

The (M)SDS is intended to provide a brief summary of our knowledge and guidance regarding the use of this material. The information contained here has been compiled from sources considered by Bridgewater LLC to be dependable and is accurate to the best of the Company's knowledge. It is not meant to be an all-inclusive document on worldwide hazard communication regulations.

This information is offered in good faith. Each user of this material needs to evaluate the conditions of use and design the appropriate protective mechanisms to prevent employee exposures, property damage or release to the environment. Bridgewater LLC assumes no responsibility for injury to the recipient of third persons, or for any damage to any property resulting from misuse of the product.

End of Material Safety Data Sheet